


Spannhülsen (Spannstifte), schwer

DIN 1481 / ISO 8752





Typ Stahl blank	Typ Edelstahl A2 ^{Rostfrei}	Nenn-Ø	l
Nenn-Ø=3; d1*=3,3; d2*=2,1; s=0,6			
1481-3x10	1481-3x10 ES	3	10
1481-3x16	1481-3x16 ES	3	16
1481-3x20	1481-3x20 ES	3	20
1481-3x26	1481-3x26 ES	3	26
1481-3x30	1481-3x30 ES	3	30
1481-3x36	1481-3x36 ES	3	36
1481-3x40	1481-3x40 ES	3	40
Nenn-Ø=4; d1*=4,4; d2*=2,8; s=0,8			
1481-4x10	1481-4x10 ES	4	10
1481-4x16	1481-4x16 ES	4	16
1481-4x20	1481-4x20 ES	4	20
1481-4x26	1481-4x26 ES	4	26
1481-4x30	1481-4x30 ES	4	30
1481-4x36	1481-4x36 ES	4	36
1481-4x40	1481-4x40 ES	4	40
1481-4x45	1481-4x45 ES	4	45
1481-4x50	1481-4x50 ES	4	50
Nenn-Ø=5; d1*=5,4; d2*=3,4; s=1			
1481-5x10	1481-5x10 ES	5	10
1481-5x16	1481-5x16 ES	5	16
1481-5x20	1481-5x20 ES	5	20
1481-5x26	1481-5x26 ES	5	26
1481-5x30	1481-5x30 ES	5	30
1481-5x36	1481-5x36 ES	5	36
1481-5x40	1481-5x40 ES	5	40
1481-5x45	1481-5x45 ES	5	45
1481-5x50	1481-5x50 ES	5	50



Typ Stahl blank	Typ Edelstahl A2 ^{Rostfrei}	Nenn-Ø	l
Nenn-Ø=6; d1*=6,4; d2*=4; s=1,2			
1481-6x10	1481-6x10 ES	6	10
1481-6x16	1481-6x16 ES	6	16
1481-6x20	1481-6x20 ES	6	20
1481-6x26	1481-6x26 ES	6	26
1481-6x30	1481-6x30 ES	6	30
1481-6x36	1481-6x36 ES	6	36
1481-6x40	1481-6x40 ES	6	40
1481-6x45	1481-6x45 ES	6	45
1481-6x50	1481-6x50 ES	6	50
1481-6x60	1481-6x60 ES	6	60
Nenn-Ø=8; d1*=8,5; d2*=5,5; s=1,5			
1481-8x10	1481-8x10 ES	8	10
1481-8x16	1481-8x16 ES	8	16
1481-8x20	1481-8x20 ES	8	20
1481-8x26	1481-8x26 ES	8	26
1481-8x30	1481-8x30 ES	8	30
1481-8x36	1481-8x36 ES	8	36
1481-8x40	1481-8x40 ES	8	40
1481-8x45	1481-8x45 ES	8	45
1481-8x50	1481-8x50 ES	8	50
1481-8x60	1481-8x60 ES	8	60

* vor dem Einbau


Bestellbeispiel andere Durchmesser und Längen: 1481-**x***



Typ einfach



Typ doppelt



Sicherungsvorstecker

ähnlich DIN 11024

Typ Stahl verzinkt	d	L	D	für Wellen-Ø
einfach				
12024-1-2	2	50	10	9 bis 14
12024-1-3	3	60	18	10 bis 16
12024-1-4	4	60	20	16 bis 20
12024-1-5	5	85	24	20 bis 28
12024-1-6	6	105	30	28 bis 40
doppelt				
12024-2-2	2	50	10	8 bis 14
12024-2-3	3	62	16	14 bis 20
12024-2-4	4	78	23	17 bis 24
12024-2-5	5	92	26	18 bis 30
12024-2-6	6	120	30	24 bis 36

Federstecker-Sortimente

Info: Federstecker finden Sie auf Seite 1016

Typ	Inhalt
FEDERSTECK SORTI	356 (2 - 2,5 - 3 - 4 - 5 - 6 - 7 mm)

